

UL1007


Hook-Up Wire 连接线

■ 产品描述

- 额定温度: 80° C
- 额定电压: 300V
- 导体: 单支或绞合 32~16AWG 镀锡或裸铜
- 绝缘: PVC
- 阻燃等级: VW-1及CSAFT1、FT2
- 参考标准: UL758 UL1581 UL2556
- 适用范围:
- 用于一般电子、电器设备内部连接线
- 颜色:
- 棕, 红, 橙, 黄, 绿, 蓝, 紫, 灰, 白, 黑, 黄/绿等

■ PRODUCT DESCRIPTION

- Rate temperature: 80° C
- Rate voltage: 300V
- Conductor: 32~16AWG (Solid or stranded, tinned or bare copper)
- Insulation: PVC
- Flame test: VW-1&CSAFT1、FT2
- Reference standard: UL758 UL1581 UL2556
- Application: For internal wiring of electronic and electrical equipment
- Color: Brown, Red, Orange, Yellow, Green, Blue, Purple, Grey, White, Black, Green/Yellow, etc



■ 印字 MARKING

AWM 1007 ()AWG 80° C 300V VW-1 E332441 YAobo cUL AWM I A 80° C 300V FT1

■ 产品结构 CABLE CONSTRUCTION



导体 CONDUCTOR			绝缘 INSULATION		最大导体电阻 MAX. COND. RESISTANCE (Ω/km, 20°C, DC)	标准长度 STANDARD PUT-UP	
规格 AWG	构造 CONSTRUCTION (No. /mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O. D. (mm)		英制 Ft/Roll	公制 M/Roll
30	7/0.1	0.30	0.40	1.10	376.96	2000	610
28	7/0.127	0.39		1.20	237.25	2000	610
26	7/0.160	0.49		1.30	148.94	2000	610
24	11/0.160	0.61		1.40	93.25	2000	610
22	17/0.160	0.76		1.60	55.0	2000	610
20	21/0.178	0.94	0.43	1.80	34.6	2000	610
18	34/0.178	1.20		2.05	21.8	2000	610
16	26/0.254	1.50		2.35	13.7	1000	305